



# EST-44/EST-44EXT

High Temperature  
Low Temperature  
44" Conveyor Dishwasher



Water Consumption  
**Only .46 Gallons**  
Per Rack of Dishes

OPTIONAL E-TEMP  
BOOSTER HEATER  
WITH 40° & 70° RISE.

OPTIONAL VENT  
HOODS

**EST-44 CONVEYOR**

Available as Right or  
Left. (must specify)



Water Consumption  
**Only .46 Gallons**  
Per Rack of Dishes

OPTIONAL E-TEMP  
BOOSTER HEATER  
WITH 40° & 70° RISE.

OPTIONAL VENT  
HOODS

**EST-44 EXT CONVEYOR**

Available as Right or Left.  
(must specify)

## FEATURES:

- ENERGY STAR® Approved.
- Automatic water control system.
- 249 racks / 996 covers per hour.
- Economical to operate. Uses only .46 gallons of water per rack of dishes.
- Single control switch activation.
- Power rinse heater system.
- Unique 3-stage washing process provides wash, power rinse and final rinse all in a 44" machine.
- Automatic soil purging system filters wash water and traps plate debris into an external tray. Tray can be easily removed for cleaning.
- All stainless steel construction offers durable performance and years of trouble-free operation.
- Chemical resistant industrial heaters are proven to be more durable than commercial grade heaters.
- Large 19" opening accommodates larger items and utensils (EST-44).
- Large 25" opening accommodates larger items and utensils (EST-44 EXT).
- Auto start/stop makes operation more energy efficient.
- Easy to remove and replace curtains for cleaning.
- Includes table limit switch and rack saver clutch system that protects the machine, dishracks and table from damage.
- 316 grade stainless steel chemical injection chamber.

## Available Options

- Corner Feed Table (left or right must specify)  
**FACTORY INSTALLED ONLY**
- Vent Hood with 4" x 16" Vent and Damper Control (2 per set) P/N: 13901.82
- Stainless Steel dishtables
- Drain Water Tempering Kit P/N: 13470.10
- "E Temp" CMA booster heater(40° and 70° rise)  
**FACTORY INSTALLED ONLY**
- Hatco Booster Heater also available (specify voltage & phase)
- Scrap Trap Single Drain Connection Kit P/N: 01321.00
- 208V-240V / 480V
- Sheet Pan Rack P/N: 1154.00
- 6" EXT height accommodates pots and pans and larger sheet pans
- Exhaust Fan Control P/N: 13578.00
- **Note: E-Temp not available single phase 70° rise.**
- **Note: E-Temp standard voltage 208-230V three phase**






# EST-44/EST-44EXT

High Temperature  
Low Temperature  
44" Conveyor Dishwasher

### WARNINGS:

- Plumbing connections must be made by a qualified service company who will comply with all available Federal, State, and Local Health, Plumbing and Safety codes.
- CMA recommends utilizing a water softening system to maintain water hardness measurements of 3.5 gpg (grains per gallon) or less. This will assure maximum results and optimum operation of the dishmachine.



### Specifications:

MODEL EST-44/44EXT H/L	USA	METRIC	USA	METRIC
<b>OPERATING CAPACITY</b> RACKS PER HOUR (NSF RATED)243	249	249	25-1/8"	(64cm)
<b>CONVEYOR SPEED</b>	6.75 FT./MIN.	(206 CM/MIN.)	44"	(111.7cm)
<b>WASH PUMP MOTORS HP</b>	1	1	55-1/2"-56-1/2"	(140.97-143.51cm)
<b>RINSE PUMP MOTOR HP</b>	1/3	1/3	61-1/2"-62-1/2"	(156-159cm)
<b>CONVEYOR MOTOR HP</b>	1/8	1/8	34"	(86cm)
<b>WATER INLET - FILL</b>	1/2"	(1.27cm)	19"	(48cm)
<b>WATER INLET - FINAL RINSE</b>	1/2"	(1.27cm)	25"	(63.5cm)
<b>DRAIN SIZE</b>	2"	(5.1cm)	<b>STANDARD DISHRACK DIMENSIONS</b>	
<b>FINAL RINSE PRESSURE</b>	20 ± 5psi	(1.41 kg/cm <sup>2</sup> )	1	1
<b>WASH TANK CAPACITY EST-44/EST-44EXT</b>			19-3/4"x19-3/4"	(50X50cm)
PRE-RINSE	4.25 GAL	(16.0 L)	<b>ELECTRICAL RATING</b>	
WASH	11.75 GAL	(44.5 L)	<b>VOLTS</b>	<b>PHASE</b>
TOTAL	16.0 GAL	(60.5 L)	208	1
<b>WASH PUMP CAPACITY</b>			240	1
EACH	52 GPM	(197 LPM)	208	3
<b>OPERATING TEMPERATURE EST-44</b>			240	3
WASH RECOMMENDED	150°F-160°F	(66°C/71°C)	480	3
PUMPED RINSE	160°F	71°C	<b>WASH TANK HEATER</b>	
FINAL RINSE	180°F-195°F	(82°C/90°C)	13kW @ 208V (3 PHASE), 13kW @ 240V (1 PHASE), 15kW@ 208V (EXT)	
<b>OPERATING TEMPERATURE EST-44</b>			<b>RINSE TANK HEATER</b>	
WASH RECOMMENDED	140°F-150°F	(60°C/68°C)	3kW @ 220V	
PUMPED RINSE RECOMMENDED	140°F-150°F	(60°C/68°C)	<b>SPECIFY DIRECTION OF RACK TRAVEL (RIGHT TO LEFT, LEFT TO RIGHT) WHEN ORDERING</b>	
FINAL RINSE RECOMMENDED	140°F-150°F	(60°C/68°C)	<b>EST-44H EXHAUST VENTILATION REQUIREMENTS AT 100% CAPACITY CFM</b>	
<b>WATER CONSUMPTION</b>			ENTRANCE END 200 MAX	DISCHARGE END 400 MAX
PER RACK (FINAL RINSE)	0.46 GAL	(1.7 L)	TOTAL CFM 600 MAX	
PER HOUR (FINAL RINSE)	114 GPH	(431 LPH)	<b>SHIPPING WEIGHT</b>	
			APPROXIMATE EST-44	662#
			APPROXIMATE EST-44EXT	687#

### Summary Specifications: Model EST-44 Conveyor

The Models EST-44H and EST-44L Chemical Sanitizing conveyor dishwashers meets ETL sanitation, UL, and CUL construction standards. The EST-44 performs three separate washing functions including a built-in power rinse, all in a 44" space. The EST-44 washes up to 249 racks per hour and uses a minimum .46 gallons of water per rack while achieving sparkling, clean, dry dishes. Constructed entirely of stainless steel.

### Call For Available Models (800-854-6417 or See web-Site: www.cmadishmachines.com

**Advisory:** CMA does NOT endorse "Tankless On-Demand" water heaters for use on CMA Dishmachine products. CMA DOES endorse, and highly recommends, the standard "tank" style water heaters, sized properly to handle each particular facility with their water heating requirements.



CMA Dishmachines 12700 Knott Street Garden Grove, CA 92841 • 800-854-6417 • 714-898-8781 • Fax: 714-895-2141 • www.cmadishmachines.com

CMA reserves the right to modify specifications or discontinue models without prior notification.

PN: 10124.30

© 6-2017 CMA, Inc.

an Ali Group Company



The Spirit of Excellence